

96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: testing@govmark.com

Page 1

Received: 12/13/2017 Completed	:12/22/2017 Letter: L3	RG P.O.#:	Test Report #:	3-23646-3-
Client's Style: Fighter. Con	mposition: 100% Polyester. W	/eight: 510 g/lm. Prod	uct End Use: Upholstery. Color #:	60082/Light Grey.
Tested For: Bente Ellingsoe,	Quality Department	Key	Test: ASTM D 4157/ACT 100K	484
Gabriel A/S				_
Hjulmagervej 55 DK-9000 Aalborg, I	Denmark		Tel: 011-45-9630-3100 I	Ext:
512 7000 11410015, 1			1 dx, 011 +3 7011 0123	
Test Category:Wyz Abrasio PC: 8H	n Specifier:ACT LE NTR 5/16	2015; VE 08/15	CODE: 100,000 RQ dl/SM	
TEST PERFORMED: ASTM D 4 (Oscillatory Cylinder Met		nod for Abrasion	Resistance of Textile Fabr	cics
As cited and modified	by the ACT Voluntary P	Performance Guide	lines (January 2015)	
cylinder of the tester. testing arms. Typically, specimens. The abradant a double rub. At specifi visually examined. The r	The submitted material two of the arms supporubs against the submied intervals, the suppesult of this visual eent's request. The te	which is to be out length specime tted material. Four arms are rail examination is rest is concluded	placed on the rotating (devaluated is held in positions, and two of the arms of a back and forth movement sed, and the submitted mat corded. The total number at the number of double runted the number of double runted to the number of double runted.	cion by four support width is considered terial is of double rubs
PRODUCT CATEGORY: Upholst	ery - Woven Fabric			
TEST PARTICULARS (check o	ne from each of items	1 - 3, as applic	able):	
<ol> <li>Abradant:</li> <li>Material with</li> </ol>	<pre>[x] #10 cotton duck ~ [ ] Wire (steel) scre</pre>		ll materials except 100% or 100% olefin	olefin
elasticity:	[ ] Backed with tape	to prevent elong	ation	
3. Surface Category:	[x] Regular surface			
	[ ] Special surface e	effect (napped, c	henille, embossed, texture	ed, etc.)
TEST CONDITIONS: Specime	n Tension: 4 lbs.; H	lead Pressure (Co	mpression Force): 3 lbs.	
RATING SYSTEM FOR REGULAR	SURFACE:			
<ul><li>5 - None or negligible</li><li>4 - Slight wear</li><li>3 - Moderate wear</li><li>2 - Noticeable wear (b</li><li>1 - Severe wear (complete</li></ul>	roken yarns, floating	yarns, etc.)		
RATING SYSTEM FOR SPECIAL	SURFACE EFFECT:			
5 - None or negligible 4 - Slight wear/change 3 - Moderate wear/chan 2 - Noticeable wear/ch 1 - Severe wear/change	of special surface ef ge of special surface ange of special surfac	ffect effect e effect (base y	arns exposed)	

(Page 1 of 2)



96-D Allen Boulevard Farmingdale, New York 11735-5626 USA Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956 e-mail: testing@govmark.com

Page 2

Received: 12/12	3/2017 Completed: 12/22/2017	Letter: L3	RG	P.O.#:	Test Report #:	3-23646-3-
Client's Style: Fighter. Composition: 100% Polyester. Weight: 510 g/lm. Product End Use: Upholstery. Color #: 60082/Light Grey.						
	ente Ellingsoe, Quality Dep abriel A/S	artment	•	Key 7	rest: ASTM D 4157/ACT 100	K 484
	ijulmagervej 55 K-9000 Aalborg, Denmark				Tel: 011-45-9630-3100 Fax: 011-45-9811-6125	Ext:

RESULTS: Visual Observations (see page 1 for Rating System)

ŦF	OI
	_

Double Rubs	Length Specimens	Width Specimens	
	4.5		
3,000	4.5	4.5	
9,000	4.5	4.5	
15,000	4.5	4.5	
22,500	4	4	
30,000	4	4	
40,000	4	4	
50,000	4	4	
60,000	3.5	3.5	
70,000	3.5	3.5	
80,000	3.5	3.5	
90,000	3.5	3.5	
100,000	3	3	
	Moderate thinning of	Moderate thinning of	
	surface yarns	surface yarns	

NOTE: For tests exceeding 100,000 double rubs, the cotton duck abradant is changed after every 100,000 double rubs.

REMARKS: None.

ACCEPTANCE CRITERIA:

Low Traffic/Private Spaces: No yarn breaks or noticeable wear after

15,000 double rubs (Minimum rating of 3)

High Traffic/Public Spaces: No yarn breaks or noticeable wear after

30,000 double rubs (Minimum rating of 3)

CONCLUSION: Based on the above Results and Acceptance Criteria, the item tested is rated for:

[x] Low Traffic/Private Spaces; [x] High Traffic/Public Spaces; [ ] Unrated

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified above.

Phyllis Pettit

JAN 0 5 2018

AUTHORIZED SIGNATURE GOVMARK

MA-5

/jb

(Page 2 of 2)