

Nepshaw Lane South, Morley, Leeds, LS27 7JQ Materials Testing Manager: Martin Bowden t: 0113 5350176 e: Materials.Testing@wyjs.org.uk www.wyjs.org.uk/materialstesting



TEST REPORT

Client:	Gabriel Hjulmagervej 55 Postbox 59 DK-9100 Aalborg Denmark
Entry No:	103855-01
Date received:	11/12/2018
Client's Description:	Xpress, 2,9mm Foam
Test Required:	Abrasion
Conditioning:	In accordance with BS EN ISO 139: 2005 for a minimum of 24 hours at 65+/-4%, Relative Humidity, 20+/-2°C
Date Tests Completed:	29/01/2019

## Abrasion Resistance: BS EN ISO 12947-2: 2016F

The tests were carried out using a pressure of 12 +/- 0.3 kPa The criterion for judging end point was three threads broken.

Specimen 1	40,000	rubs
Specimen 2	40,000	rubs
Specimen 3	50,000	rubs
Specimen 4	50,000	rubs
<b>Overall Result</b>	40,000	rubs
n colour after 6,000 rubs:	4-5	

Change in colour after 6,000 rubs:

Observation Technique: Type of Fabric:

10 fold magnification Flat Woven

-----End of Document------

This is hereby certified to be a correct return of the tests made of the items referred to herein

mille

**Claire Saville** Technologist 29th January 2019

Unless instructed otherwise by the client sample remnants will be disposed of after 28 days.

Tests marked <sup>N</sup> in this certificate are not included in the UKAS Accreditation Schedule for this Laboratory. Tests marked <sup>S</sup> in this certificate are performed under the Laboratory's Flexible Scope of Accreditation. Tests marked <sup>S</sup> in this certificate have been subcontracted to another ISO17025 Accredited Laboratory.

- ÷ ÷
- ٠
- Opinions and interpretations expressed herein are outside the scope of UKAS accreditation.

Uncertainty budgets for test methods contained within this report are available on request.

This Certificate relates only to the sample received and, unless that sample has been drawn by the staff of this laboratory, or its agent, and endorsed accordingly, any application of the result to a bulk quantity or other material is entirely the responsibility of the client.



