

Nepshaw Lane South, Morley, Leeds, LS27 7JQ Materials Testing Manager: Martin Bowden t: 0113 5350176 e: Materials.Testing@wyjs.org.uk www.wyjs.org.uk/materialstesting



TEST REPORT

Client:	Gabriel Hjulmagervej 55 Postbox 59 DK-9100 Aalborg Denmark					
Entry No:	113786-02					
Date received:	19/11/2019					
Client's Description:	Fabric: Swing 51404. Composition: 54%Wool/ 44% PES/ 2% PA					
Test Required:	Flammability					
Pre-treatment:	None					
Conditioning:	A minimum of 24 hours at 50+/-5% Relative Humidity, 23+/-2°C					
Date Tests Completed:	26/11/2019					
Method of Test:	BS EN 1021-1:2014 – smouldering cigarette BS EN 1021-2:2014 – match flame equivalent					

The following test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

Ignition Source	Observations	Result
Smouldering	No flaming or progressive smouldering was observed within one hour of	Pass
cigarette	placement of the cigarettes.	
Match flame equivalent	Flaming ceased within the specified two minute period after removal of the butane flame and no progressive smouldering occurred.	Pass

Note: 35 kg/m3 CMHR Foam was used as the filling

The above tests relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

------End of Page------

This is hereby certified to be a correct return of the tests made of the items referred to herein

Daniel Young Senior Technologist 06 January 2020

- Unless instructed otherwise by the client sample remnants will be disposed of after 28 days.
- Opinions and interpretations expressed herein are outside the scope of UKAS accreditation.

Tests marked ^F in this certificate are performed under the Laboratory's Flexible Scope of Accreditation. Uncertainty budgets for test methods contained within this report are available on request. * *

The results have been obtain for the above test are due to the allowances that have been made based on the uncertainty of the measurement for this test and its associated measurements.

This Certificate relates only to the sample received and, unless that sample has been drawn by the staff of this laboratory, or its agent, and endorsed accordingly, any application of the result to a bulk quantity or other material is entirely the responsibility of the client.







Client: Gabriel

Entry No: 113786-02



During the tests the following data was recorded: -

	Smouldering cigarette			Match flame equivalent		
Time of Ignition (sec)	No Ignition	No Ignition	No Ignition	7	7	7
Time to extinction of flame after	N/A	N/A	N/A	16	17	17
removal of butane flame (sec) Time of Cover Split (sec)	No split	No split	No split	11	10	9
Melting (Yes or No)	Yes	Yes	Yes	Yes	Yes	Yes
Dripping (Yes or No)	No	No	No	No	No	No
Charring (Yes or No)	Yes	Yes	Yes	Yes	Yes	Yes
Self-extinguished before smouldering full length (Yes or No)	Yes	Yes	Yes	N/A	N/A	N/A
Other phenomena						

-----End of Document-----

