

Page 1

Received: 05/04/2020 | Completed: 05/05/2020 | Letter: H1 BG | P.O.#: Test Report #: 3-38364-1-RV Style: Contour. Content: 100% PBT. Finish: None. Weight: 380 g/m². Color #: 60158 Dark Grey. Product End Use: Client's Identification Upholstery. Tested For: Alvyda Kraulediene Key Test: CA TB 117-2013 (Section 1-Cover Gabriel A/S Fabric) /ACT RVNC Hjulmagervej 55 Tel: 011-45-42134509 Ext: DK-9000 Aalborg, Denmark Fax:

Test Category: Cigarette Ignition

Specifier: ACT

LE 2019; V 12/19 NTR 9/15

dl/SM

Product Category: Upholstery

PC: 24H

TEST PERFORMED: California Technical Bulletin 117-2013 - Requirements, Test Procedure and Apparatus for Testing the Smolder Resistance of Materials Used in Upholstered Furniture (June 2013 Version; V 1/19)

Section 1, Cover Fabric Test (Upholstery cover material is the outermost layer of fabric or related material used to enclose the main support system or upholstery materials, or both, used in the furniture item.) --

As cited by the ACT Voluntary Performance Guidelines (March 2019)

REFERENCE: ASTM E1353-08ae1

IGNITION SOURCE: SRM 1196a Cigarette

## SPECIMEN TEST COMPOSITE:

Upholstery Cover Material: As described in "Client's Identification".

Standard Substrate Material: Non FR polyurethane foam, density 1.8 ± 0.05 lb/ft3

BRIEF DESCRIPTION OF TEST: Miniature cushions are prepared using the client's cover fabric over the standard filling material. The vertical or back cushions measure  $8" \times 8" \times 2"$ . The horizontal or seat cushions measure  $8" \times 5" \times 2"$ .

A lighted cigarette is placed in the crevice formed by the vertical cushion and the horizontal cushion.

The test is terminated at 45 minutes if smoldering is no longer observed.

Test measurements and observations are recorded.

-- See Page 3 for "Results" and "Conclusion" --

(Page 1 of 4)



Page 2

Received: 05/04	/2020 Completed: 05/05/2020	Letter: H1	BG	P.O.#:	Test Report #:	3-38364-1-RV
Client's Identification	Style: Contour. Content: 100% Upholstery.	PBT. Finish: N	one. W	eight: 380 g/m². Color #	: 60158 Dark Grey. Pro	oduct End Use:
Tested For: Al	vyda Kraulediene			Key Test: C	CA TB 117-2013 (Secti	ion 1-Cover
Ga	abriel A/S			F	abric) /ACT RVNC	
Hj	ulmagervej 55			Tel: 0	11-45-42134509	Ext:
DI	K-9000 Aalborg, Denmark			Fax:		

PASS/FAIL/REPEAT CRITERIA: A material is considered to pass or fail based on the following criteria:

- 1. A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs:
  - a) The mock-up test specimen continues to smolder after the 45 minute test duration;
  - b) A vertical char length (measured as specified in step 11.9 of ASTM E1353-08ael) of more than 1.8 inches (45 mm) develops on the cover fabric.
  - c) The mock-up test specimen transitions to open flaming.
- 2. The cover fabric passes the test if three initial mock-up specimens pass the test, i.e., the cigarettes burn their entire length and the mock-ups are no longer smoldering.
- 3. If more than one initial specimen fails, the cover fabric fails the test.
- 4. If any one of the three initial specimens fails, repeat the test on additional three specimens.
- 5. If all three additional specimens pass the test, the cover fabric passes the test. If any one of the additional three specimens fails, the cover fabric fails the test.

DISCUSSION: The current version of California Technical Bulletin 117-2013 has no provision to recognize cigarettes that self-extinguish prior to burning their entire length. However, ASTM E1353 does recognize this phenomenon.

The SGS North America report evaluates replacement cigarettes as follows:

If a cigarette self-extinguishes (SE) before burning its entire length, a new cigarette is placed into the test. If the new (replacement) cigarette self-extinguishes or burns its entire length, the result for that specimen will then be evaluated as if the cigarette burned its entire length when assigning the "Passing /Failure" conclusion.



Page 3

Received: 05/04/2020	Completed: 05/05/	2020 Letter: H1	BG <b>P.O.</b> #:	Те	est Report #:	3-3836	4-1-RV	
Client's Style: Identification Uphol		00% PBT. Finish: Non	e. Weight: 380 g/m <sup>2</sup>	<sup>2</sup> . Color #: 60158	Dark Grey. Pro	duct End Use	:	
Tested For: Alvyda Gabriel Hjulmag DK-900	A/S	k	Ke	y Test: CA TB 1 Fabric) // Tel: 011-45-4 Fax:	ACT RVNC	on 1-Cover  Ext:		
RESULTS:		Char Length	SE	SB45	TOF			
	Specimen #	(inches)	(yes/no)	(yes/no)	(yes/no)			
Initial:	1 2 3	0.5 0.5 0.4	No No	No No No	No No			
Replacement: (If needed)	1 2 3							
Repeat Tests: (If needed)	1 2 3							
EXPLANATION:								
Initial:		first 3 cigarette draw a test concl		sults could be	е			
Replacement:	If any of the initial cigarettes self-extinguish before burning their complete length, a new test is conducted with a fresh cigarette.							
Repeat Test:	Repeat Test: Depending on the initial or replacement results, 3 repeat tests might be required to draw a conclusion.							
CODES USED:								
SB45 = Smolde TOF = Transi MNR = Measure transi EC = Escala	r beyond 45 min tions to open to ement not recon tioned to open ting smoldering	laming ded as smoldering	exceeded 45 m	inutes or spe	cimen			
CONCLUSION: The above resulfficient to	7	for the initial an	nd/or replacemen	nt cigarettes	are			
[x] Passin	g; [] Failure	e; [] Repeat test	on 3 addition	al specimens				
The results a	fter conducting	g the repeat tests	indicate:					
[] Passin	g; [ ] Failure	(Page	3 of 4)					



Page 4

Received:05/0	4/2020	Completed: 05/05/2020	Letter: H1	BG	P.O.#:	Test Report #:	3-38364-1-RV
Client's Identification			PBT. Finish: Nor	ne. We	eight: 380 g/m². Color #: 601	58 Dark Grey. Produ	ict End Use:
Tested For: Alvyda Kraulediene Key Test: CA TB 117-2013 (Section 1-Cover						1-Cover	
	Gabriel .	A/S			Fabric	c) /ACT RVNC	
I	Ijulmag	ervej 55			<b>Tel:</b> 011-4	5-42134509	Ext:
Ι	K-900	0 Aalborg, Denmark			Fax:		

REMARKS: None.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified above.

> RV.07.09.20 /gb

> > JUL 1 5 2020

AUTHORIZED SIGNATURE SGS North America

/gb

Phyllis Pettit

(Page 4 of 4)