

Nepshaw Lane South, Morley, Leeds, LS27 7JQ Materials Testing Manager: D. J. Brockbank

t: 0113 393 9791

e: dale.brockbank@wyjs.org.uk www.wyjs.org.uk/materialstesting



TEST REPORT

Client: Gabriel

Hjulmagervej 55 Postbox 59 DK-9100 Aalborg

Denmark

Entry No: 93320

Date received: 13/12/2017

Client's Description: Sample of fabric: Europost 60003 Grey

Test Required: Flammability BS 5852: 1979 Ignition sources 0 & 1

Pre-treatment: None

Conditioning: A minimum of 96 hours at 50+/-20% Relative Humidity, 20+/-5°C

Date Tests Completed: 03/01/2018

Method of Test: BS 5852: Part 1: 1979

The following test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

| Ignition Source | Observations | Result |
|------------------|--|--------|
| 0 (cigarette) | No flaming or progressive smouldering was observed within one hour of | PASS |
| | placement of the cigarettes. | |
| 1 (butane flame) | Flaming ceased within the specified two minute period after removal of the | PASS |
| | butane flame and no progressive smouldering occurred. | |

Note: A 20-22 kg/m3 non fire retardant polyurethane foam was used as the filling

During the tests the following data was recorded: -

| | Source 0 | | Source 1 |
|-----------|----------|------------|----------|
| 1 141 / \ | N. 1 141 | A.1 1 1/21 | |

| Time of Ignition (sec) | No Ignition | No Ignition | 1 | 1 |
|-----------------------------------|---------------|---------------|---------------|---------------|
| Time to extinction of flame after | N/A | N/A | 1 | 1 |
| removal of butane flame (sec) | | | | |
| Time of Cover Split (sec) | Did Not Split | Did Not Split | Did Not Split | Did Not Split |
| Melting (Yes or No) | Yes | Yes | Yes | Yes |
| Dripping (Yes or No) | No | No | No | No |
| Charring (Yes or No) | Yes | Yes | Yes | Yes |

This is hereby certified to be a correct return of the tests made of the items referred to herein

Dale Brockbank

Materials Testing Manager

03 January 2018

- Unless instructed otherwise by the client sample remnants will be disposed of after 28 days.
- Opinions and interpretations expressed herein are outside the scope of UKAS accreditation.
- Uncertainty budgets for test methods contained within this report are available on request.
 This Cortificate relates only to the cample received and unless that sample has been drawn by

This Certificate relates only to the sample received and, unless that sample has been drawn by the staff of this laboratory, or its agent, and endorsed accordingly, any application of the result to a bulk quantity or other material is entirely the responsibility of the client.





