
Report Reference: TR5216/206700



F.A.O: Bente Ellingsoe

Order Date: 27th February 2018 Order No: None Given

Date of Receipt: 27th February 2018

Items Tested: Cura

Colour: 61168
Style No: Art. 2480
End Use: None Given

Claimed: 98% Post-consumer Recycled Polyester, 2% Polyester

Bureau Veritas

Services UK Ltd 31 Kingsland Grange

Consumer Products

Woolston Warrington Cheshire

WA1 4RW

Specifications: Tests as per BS 14465: 2003

TEST	METHOD	PASS	FAIL	
Fastness to Washing	BS EN ISO 105-C06:2010 - C2S @ 60°C	See Results		
Fastness to Dry Cleaning	BS EN ISO 105-D01:2010	See Results		
Fastness to Rubbing	BS EN ISO 105-X12:2016	See Results		
Fastness to Light	BS EN ISO 105-BO2:2014-BS7 – Method 2	See Results		
Seam Slippage – Upholstery	BS EN ISO 13936-2:2004	See Re	esults	
Determination of Elasticity – 27.5N Load	BS EN 14704-1:2005	See Re	esults	
Tensile Strength of Fabrics. Strip Method.	BS EN ISO 13934-1:2013	See R	esults	
Tear Strength - Elmendorf	BS EN ISO 13937-1:2000	See Re	esults	
Dimensional Stability to Washing	BS EN ISO 6330 : 2012 6M @ 60°C Flat Dry	See Results		
Flammability	EN ISO 1021-1 & 2 :2014 \$	See R	esults	
\$ Sub-contracted Test				

Results: As detailed in this report

Observations: Results taken from test report number 204202

Authorised By: C. Clarke

Issue Date: 8th March 2018

Report Reference: TR5216/206700

Items Tested: Cura

Colour: 61168 Style No: Art. 2480 End Use: None Given

Claimed: 98% Post-consumer Recycled Polyester, 2% Polyester

Date of Receipt: 27th February 2018

<u>Date of Test:</u> 27th February 2018

<u>Test Specification:</u> As listed on previous page

Deviations: None

Colours Assessed: A=61168									
		RESULTS							
		STAINING							
TEST	Colour	C.I.S.	Acetate	Cotton	Nylon	Polyester	Acrylic	Wool	REQUIREMENTS
Fastness to Washing	A	4/5	4/5	4/5	4/5	4/5	4/5	4/5	None Specified
Fastness to Dry Cleaning	A	4/5	4/5	4/5	4/5	4/5	4/5	4/5	None Specified
Fastness to Rubbing			Dry		Wet			None Specified	
rastness to Kubbing	A	-	4/5 4/5		None Specified				
Fastness to Light	A	BS7 @ GS4 = >BS7			None Specified				

C.I.S = Change In Shade

C. Clarke

Softlines Assistant Manager

4. Im

Report Reference: TR5216/206700

Items Tested: Cura

Colour: 61168
Style No: Art. 2480
End Use: None Given

Claimed: 98% Post-consumer Recycled Polyester, 2% Polyester

<u>Date of Receipt:</u> 27th February 2018

<u>Date of Test:</u> 27th February 2018

<u>Test Specification:</u> As listed on previous page

Deviations: None

TEST	RESULT	REQUIREMENTS	°C	%RH
Seam Slippage – Upholstery	Warp Slippage: 2.5 mm seam opening @ 180 N Weft Slippage: 3.0 mm seam opening @ 180 N	None Specified	20°C (+/- 2°C)	65% RH (+/- 4%)
Determination of Elasticity – 27.5 N Load	Residual Extension After 1 Minute Warp: 0.0 % Weft: 0.0 % Residual Extension After 30 Minutes Warp: 0.0 % Weft: 0.0 % Extension at 27.5 N Warp: 8.5% Weft: 5.9%	None Specified	20°C (+/- 2°C)	65% RH (+/- 4%)
Tensile Strength of Fabrics. Strip Method	Warp: 1769.0 N Weft: 1551.0 N	None Specified	20°C (+/- 2°C)	65% RH (+/- 4%)
Tear Strength - Elmendorf	Warp: Result of 3: >64 N Weft: Result of 3: >64 N	None Specified	20°C (+/- 2°C)	65% RH (+/- 4%)
Dimensional Stability to Washing	Warp: -0.3 % Weft: -0.7 %	None Specified	20°C (+/- 2°C)	65% RH (+/- 4%)

C. Clarke

Softlines Assistant Manager

A. Im

Report Reference: TR5216/206700

Items Tested: Cura

Colour: 61168 Style No: Art. 2480 End Use: None Given

Claimed: 98% Post-consumer Recycled Polyester, 2% Polyester

<u>Date of Receipt:</u> 27th February 2018

<u>Date of Test:</u> 27th February 2018

Test Specification: As listed on previous page

Deviations: None

Test Results

Test Results -

Ignition source Smouldering Cigarette

ignition source Smouldering Cigarette				
Criteria of ignition	Cigarette 1	Cigarette 2		
Progressive smouldering ignition Clause 3.1a – test assembly displays escalating combustion behaviour so that it is unsafe to continue.	No	No		
Clause 3.1b – test assembly that smoulders until it is largely consumed	No	No		
Clause 3.1c – test assembly that smoulders to the extremities within the test duration	No	No		
Clause 3.1d – test assembly that smoulders after one hour from application of the ignition source	No	No		
Clause 3.1e – test assembly on final examination shows evidence of progressive smouldering	No	No		
Flaming Ignition Occurrence of flames initiated by a smouldering source	No	No		
Ignition occurring	Non – Ignition	Non - Ignition		

Report Reference: TR5216/206700

Items Tested: Cura

Colour: 61168 Style No: Art. 2480 End Use: None Given

Claimed: 98% Post-consumer Recycled Polyester, 2% Polyester

Date of Receipt: 27th February 2018

Date of Test: 27th February 2018

Test Specification: As listed on previous page

Deviations: None

rest Results

Ignition source Match Flame

Ignition source Match Flame					
Criteria of ignition	Match Flame 1	Match Flame 2			
Progressive smouldering ignition Clause 3.1a – test assembly displays escalating combustion behaviour so that it is unsafe to continue.	No	No			
Clause 3.1b – test assembly that smoulders until it is largely consumed	No	No			
Clause 3.1c – test assembly that smoulders to the extremities within the test duration	No	No			
Clause 3.1d – test assembly that smoulders after one hour from application of the ignition source	No	No			
Clause 3.1e – test assembly on final examination shows evidence of progressive smouldering	No	No			
Flaming Ignition Clause 3.2a – Test assembly displays escalating combustion behaviour so that it is unsafe to continue	No	No			
Clause 3.2b – Test assembly burns until it is essentially consumed	No	No			
Clause 3.2c – Flame reaches the lower margin, either side or passed through the full thickness	No	No			
Clause 3.2d – Flaming continues for more than 120 seconds after removal of burner tube	No	No			
Ignition occurring	Non – Ignition	Non - Ignition			

The test specimen was tested over Combustion modified foam (CMHR) with a density of 35kg/m³.

The above test results relate only to the ignitability of the combination of materials under particular conditions of test; they are not intended as a means of assessing the full fire hazard of the materials in use.

C. Clarke

Softlines Assistant Manager

A. Im



Tests marked 'Not UKAS Accredited' in this report are not included in the UKAS schedule for this laboratory. Opinions and interpretations expressed herein are outside the scope of the UKAS Accreditation. Where the results of a test fall close to the requirement, either above or below, compliance with the specification may be affected by the uncertainty of measurement of the test. In those circumstances, the laboratory can be contacted for further information.

uncertainty of measurement of the test. In those circumstances, the laboratory can be contacted for further information.

The information contained within any report is based on current BVCPS UK Ltd knowledge and is given without guarantee. A satisfactory test report in no way implies that the product so tested is approved by BVCPS UK Ltd, UKAS or other body.

A report is a confidential document to the person or firm to whom it is issued and it will be strictly treated as such by BVCPS UK Ltd. It may not be reproduced either in its entirety or in part and may not be used for advertising. The person or firm to whom the report is issued may however show it or send it, or a certified copy thereof prepared by BVCPS UK Ltd, for the information of his customer, supplier or other persons directly concerned. BVCPS UK Ltd will not, without the written consent of the person or firm, enter into any discussion or correspondence with any third party concerning the contents of the report. In the event of the improper use of a report, BVCPS UK Ltd reserves the right to withdraw it or adopt any other remedy which may be appropriate.

Samples submitted for testing are accepted on the understanding that the report issued shall not form the basis of, or instrument for, any legal liability against BVCPS UK Ltd and applies specifically to the sample(s) tested and not necessarily to the bulk.

Bureau Veritas Consumer Products Services UK Ltd, Registered in England & Wales, Company Number: 00852439 Registered Office: 31 Kingsland Grange, Woolston, Warrington, Cheshire, WA1 4RW